



## Traffic Control Plan

Site Address: 7900 Wisconsin Ave. Bethesda, MD.

Drawing not to scale

Comments: Working from the east curb of Woodmont Ave between St. Elmo & Norfolk Ave.

**Note: Sidewalks on both east and west side of Woodmont Ave will remain open at all times for pedestrians to access businesses**



## SIGN SPACING GUIDE

SPEED (mph)	MIN. SIGN SPACING (ft)
25	150
30	200
35	250
40	350
45	550
50	600
55	700

**STANDARD NOTES:**

1. Parking is to be restricted 72 hours in advance, unless there is an emergency.
2. Signs shall be installed prior to the commencement of all work, and removed immediately after completion of activities.
3. If a sign is no longer required it will be removed or covered.
4. Signs must be FHWA Approved / NCHRP - 350 Rated.
5. Signs shall be mounted on spring-loaded sign stands or devices that meet current crash test rating approval as indicated in the current MUTCD or by current FHWA Standards.
6. Work Zones must adhere to the "Guidelines and Standards for Temporary Traffic Control" issued on the jurisdictional standards as the current "Manual on Uniform Traffic Control Devices (MUTCD)" and all its amendments that are issued by the Federal Highway Administration (FHWA).

### Legend

-  Work Area
-  Barrier
-  Sign Stand
-  48"x48" Retroreflective Sign
-  Cone
-  flagger
-  semi trailer
-  Crane